

Fuji USER MANUAL

DRILLS

MODELS : FRD-5S-1, -1F, -2T, 2TF



FRD-5S-1
FRD-5S-2T



FRD-5S-1F
FRD-5S-2TF

SPECIFICATIONS

Model	Drilling Capacity		Stall Torque			Rotational Frequency	Type and Size of Spindle		Chuck Capacity (mm)		Distance from Center to Side		Overall Length		Mass		Max. Air Consumption	
	mm	in	N·m	kgf·m	ft·lb	min ⁻¹	Thread	Taper	Thread	Taper	mm	in	mm	in	kg	lb	m ³ /min	ft ³ /min
FRD-5S-1	5	3/16	2.0	0.20	1.4	3,200	3/8-24	—	6.5	—	18.5	47/64	188	7 ¹³ /32	0.6	1.3	0.60	21.2
FRD-5S-1F	5	3/16	2.0	0.20	1.4	3,200	3/8-24	—	6.5	—	18.5	47/64	188	7 ¹³ /32	0.6	1.3	0.60	21.2
FRD-5S-2T	2	5/64	0.3	0.03	0.2	24,000	—	J.T.#D	—	5.0	18.5	47/64	174	6 ⁵⁵ /64	0.5	1.1	0.60	21.2
FRD-5S-2TF	2	5/64	0.3	0.03	0.2	24,000	—	J.T.#D	—	5.0	18.5	47/64	174	6 ⁵⁵ /64	0.5	1.1	0.60	21.2

Air Inlet Thread Size : PT or NPT 1/4". Air Hose Size : 6.3mm (1/4").

The performance figures are at 0.63MPa (6.3bar).

⚠ Refer to "The Instructions and Warning for Safety Use" enclosed in each tool box.

Fuji Industrial Technique Co.,Ltd.

2-1-14, Kamiji, Higashinari-ku, Osaka, 537-0003 Japan

Tel : 81-6-6972-2335

Fax : 81-6-6972-2380

